

To get connected to the  
Goodyear Race Tire Distributor nearest you, dial

**1-877-881-RACE**

Or call your nearest Distributor direct.

**WEST**

Carroll Shelby Enterprises, Inc.  
6775 Speedway Blvd.  
Bldg. M107  
Las Vegas, NV 89115-1720  
Phone: 702-430-5160  
Fax: 702-430-5167  
www.carrollshelbyent.com

**EAST**

Competition Tire East, Inc.  
150 Franklin St.  
P.O. Box 1056  
Reading, PA 19603-1056  
Phone: 610-375-6191  
Fax: 610-375-0196

**MIDWEST**

Competition Tire West, Inc.  
12666 US 12  
P.O. Box 666  
Brooklyn, MI 49230  
Phone: 517-592-6681  
Fax: 517-592-3696

**SOUTHEAST**

Huggins Tire Sales, Inc.  
3801 North Main St.  
High Point, NC 27265  
Phone: 336-869-2211 or 2913  
Fax: 336-885-7623

**SOUTHWEST**

Carter-Maxwell, Inc.  
4215 N. Wilburn Ave.  
Bethany, OK 73008  
Phone: 405-789-8253  
Fax: 405-789-9201

**SOUTH**

Competition Tire South, Inc.  
771-28 Fentress Blvd.  
P.O. Box 11586  
Daytona Beach, FL 32120-1586  
Phone: 386-274-5332  
Fax: 386-274-5442

**CANADA**

Competition Tire Canada  
360 York Rd.  
RR # 4  
Niagara On The Lake  
Ontario, Canada L0S1J0  
Phone: 905-684-7418  
Fax: 905-684-1774

**SHORT TRACK SALES**

Larry Robinson Enterprises  
Larry Robinson  
2632 S.W. Bear Paw Trail  
Palm City, FL 34990  
Phone: 561-333-0082  
Fax: 561-798-0380  
Email: lreinc@bellsouth.net



For current suggested retail prices, visit

[www.racegoodyear.com](http://www.racegoodyear.com)

©2008 The Goodyear Tire & Rubber Company. All rights reserved.

034110-11/08



Eagle® Racing Tire Guide | 2009

ROUTING	
AD	_____
<input type="checkbox"/> Spellchecked	_____
<input type="checkbox"/> Files in server	_____
Proof	_____
Copy	_____
CD	_____
GS	_____
<input type="checkbox"/> Spellchecked	_____
<input type="checkbox"/> Files in server	_____
CPC	_____
AS#1	_____
AS#2	_____
Client	_____
DirProd	_____
Buyer	_____
*****	
<b>IMAGE VERIFICATIONS</b>	
• Legal Usage Rights	
• Image Resolution	
• FPO indications	
• Competitor check	
*****	
<b>NEXT STEP:</b>	
BW	Color
P_PDF	X_PDF
Pkg for FA	



# General Information

## No Warranty

Due to the conditions under which they operate, Goodyear MAKES NO WARRANTY AND SPECIFICALLY DISCLAIMS ANY WARRANTY (INCLUDING ANY WARRANTY AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), EITHER EXPRESSED OR IMPLIED, with respect to Goodyear Racing Tires, tubes, safety spares or air containers and shall not be liable for any damages whatsoever including, without limitation, consequential or special damages, arising out of their use. Goodyear Racing Tires are designed and compounded solely for racing purposes and are not tested or labeled to meet FMVSS/ECE Regulations. It is therefore not only dangerous but also illegal to sell for use or use race tires on public streets or highways.

## Pressure Recommendations

Consult your Goodyear Racing Tire Distributor for specific recommendations for your local track.

Tire changing should be done by trained personnel using proper tools and procedures. **NEVER** attempt to install and inflate a tire of one diameter on a rim or wheel of another diameter. All Goodyear Racing Tires are designed to be used on wheels or rims that are manufactured to Tire and Rim Association (T&RA) specifications and tolerances. Use of Goodyear Racing Tires on damaged or improper rims can cause the assembly to explode with force sufficient to cause injury or death. When inflating, always lock wheel on mounting machine or place in safety cage and use extension gauge and hose clip on air chuck. **STAND BACK. NEVER EXCEED 35 PSI TO SEAT BEADS.**

## Tire Care

Goodyear Racing Tires should not be stored near high temperature, in direct sunlight, around welding areas, in overhead garage areas or around high-voltage electric motors. Long-term storage of Goodyear Racing Tires is not recommended.

**NEVER** attempt to patch or repair a Goodyear Racing Tire.

**NEVER** attempt to chemically or physically treat or alter a Goodyear Racing Tire.

**NEVER** re-use a Goodyear Racing Tire involved in a vehicle fire under **ANY** circumstances.

## Tire Specifications

Size designations on Goodyear Racing Tires show nominal outside diameter, tread width and bead diameter (e.g., 27.0x9.0-15). All dimensions are taken from an inflated tire under no load conditions.

Our comprehensive line of Goodyear Racing Tires brings versatility to the racing fraternity. Each type of racing activity is provided with a choice of tires affording the ultimate in performance during acceleration, cornering and braking.

The increasing successes of Goodyear Racing Tires in worldwide competition give testimony to the effort in development, design and production of this extensive line.

A choice of compounds is available for some types of racing to best suit given track conditions. Consult your nearest Goodyear Racing Tire Distributor for specific recommendations for any particular vehicle or track in your area.

## Additional Information

Additional information can be found at [www.racegoodyear.com](http://www.racegoodyear.com).

# Eagle® Dragway Special®

## Eagle Dragway Special Eagle Drag Radial Eagle Drag Motorcycle

- Large selection of sizes, compounds and constructions for all applications
- Minimal break-in required
- Long lasting to help lower tire expenses
- Proven performance over a wide range of track conditions



Eagle Dragway Special

Eagle Drag Radial



Eagle Drag Motorcycle

Product Code	Size	Soft To Harder →		Rec. Rim Width* (in.)	Overall Diameter (in.)	Average Circumference (in.)	Section Width (in.)	Tread Width (in.)	Recommended Rim Type	Weight (lbs.)
<b>Top Fuel, Funny Car</b>										
D-2E										
808-018-081 MATL. NO.	36.0X17.5-16	2550 208039		16.0	36.0	115.0	21.6	17.3	BEADLOCK	49.1
<b>Pro Stock</b>										
D-4A										
808-043-081 MATL. NO.	33.5X17.0-16	2200 193251		16.0	33.8	105.0	20.8	17.4	BEADLOCK	43.1
<b>Alcohol, Funny Car, Pro Mod</b>										
D-2A    D-11    D-1    D-2										
808-117-081 MATL. NO.	34.5X17.0-16	1022-3 176052		16.0	34.8	109.0	21.0	17.0	BEADLOCK	42.1
808-117-081 MATL. NO.	34.5X17.0-16		1490 23530	16.0	34.8	109.0	21.0	17.0	BEADLOCK	45.3
808-276-081 MATL. NO.	36.0X17.0-16		2540 206845	16.0	36.2	114.0	21.4	17.0	BEADLOCK	46.8
808-276-081 MATL. NO.	36.0X17.0-16			16.0	36.2	114.0	21.4	17.0	BEADLOCK	48.5
										3199 121937

\*Acceptable application for rim width is tread plus or minus one inch

# Eagle® Dragway Special®

# Eagle® Dragway Special®

Product Code	Size	Soft To Harder →	Rec. Rim Width* (in.)	Overall Diameter (in.)	Average Circumference (in.)	Section Width (in.)	Tread Width (in.)	Recommended Rim Type	Weight (lbs.)
--------------	------	------------------	-----------------------	------------------------	-----------------------------	---------------------	-------------------	----------------------	---------------

Product Code	Size	Soft To Harder →	Rec. Rim Width* (in.)	Overall Diameter (in.)	Average Circumference (in.)	Section Width (in.)	Tread Width (in.)	Recommended Rim Type	Weight (lbs.)
--------------	------	------------------	-----------------------	------------------------	-----------------------------	---------------------	-------------------	----------------------	---------------

## Stock, Super Stock

	D-4A	D-6	D-5	D-3						
808-735-081 MATL. NO.			#	2000-4 190166	8.0	28.0	88.0	10.7	9.0	21.3
808-736-081 MATL. NO.			#	2001-4 190824	10.0	28.0	88.0	12.0	10.0	23.1
808-149-081 MATL. NO.			#	2502-4 202897	10.0	28.0	88.0	12.5	10.7	24.4
808-172-081 MATL. NO.			#	2003-4 190799	8.0	29.0	91.0	10.9	9.0	21.0
808-173-081 MATL. NO.			#	2004-4 190800	10.0	29.0	91.0	11.8	10.0	23.0
808-174-081 MATL. NO.			#	2006-4 190164	10.0	29.0	91.0	12.8	10.9	25.1
808-188-081 MATL. NO.			#	2007-4 190165	11.0	29.0	91.0	13.9	11.8	26.3
808-717-081 MATL. NO.		2120 192096			8.0	30.0	94.0	11.6	9.0	25.4
808-717-081 MATL. NO.			1909 23623		8.0	30.7	96.5	12.4	9.0	25.0
808-739-081 MATL. NO.			2009 190826		10.0	30.0	94.0	13.0	10.2	27.6
808-719-081 MATL. NO.			2016 190823		10.0	30.1	94.0	13.8	11.4	29.0
808-214-081 MATL. NO.			2017 190822		12.0	30.2	95.0	15.2	12.4	30.2
808-096-081 MATL. NO.			2018 190161		12.0	30.6	96.0	15.6	12.8	33.4
808-097-081 MATL. NO.			2019-1 190162		12.0	31.0	97.0	16.2	14.0	35.8
808-266-081 MATL. NO.		1823 189702			14.0	31.8	100.0	18.2	14.7	34.1
808-178-081 MATL. NO.			1984-1 23556		14.0	32.4	101.0	17.0	14.4	39.3
808-163-081 MATL. NO.			1672-1 23540		14.0	32.8	103.0	17.7	14.8	39.4
808-779-081 MATL. NO.		1831-2 190758			14.0	32.7	102.0	18.3	14.0	34.9
808-164-081 MATL. NO.			2070 190163		14.0	32.8	104.0	18.9	14.9	34.1

## Motorcycle

	D-9	D-6	D-3	HARD						
808-036-919 MATL. NO.				2322 197804	2.5	23.3	73.5	3.3	4.3	5.1
808-351-919 MATL. NO.			2084-8 192095		5.0	25.4	80.0	6.1	5.3	9.7
808-891-919 MATL. NO.		2980-8 103310	2982-8 103311		6.0	25.4	80.0	7.0	6.6	11.3
808-194-919 MATL. NO.		2175 191717			9.0	26.4	83.0	11.6	10.0	20.3

## Super Gas, Super Street

	D-1	D-4A	D-6	D-5						
808-178-081 MATL. NO.			1160-1,3 164658		14.0	32.4	102.0	17.0	14.4	34.2
808-184-081 MATL. NO.			2252-1,3 193644		15.0	32.4	102.0	18.4	16.0	35.3
808-178-081 MATL. NO.				1984-1 23556	14.0	32.4	101.0	17.0	14.4	39.3
808-163-081 MATL. NO.				1672-1 23540	14.0	32.8	103.0	17.7	14.8	39.4
808-184-081 MATL. NO.				1408-1 23558	15.0	32.4	102.0	18.4	16.0	39.6
808-260-081 MATL. NO.				2078-1 192212	14.0	33.2	104.0	17.5	15.0	40.6
808-801-081 MATL. NO.				2079-1 192213	14.0	33.6	106.0	17.8	15.1	39.2
808-031-081 MATL. NO.				2051-1,3 190102	15.0	32.5	100.0	20.8	17.2	41.1
808-031-081 MATL. NO.				2053-1 191202	15.0	32.8	102.0	20.6	17.3	42.9
808-031-081 MATL. NO.				2556 23509	15.0	32.8	102.0	20.5	17.3	41.0

\*Acceptable application for rim width is tread plus or minus one inch

\*Acceptable application for rim width is tread plus or minus one inch  
# - To be announced.

# Eagle® Dragway Special®

# Eagle® Dragway Special®

Product Code	Size	Soft To Harder →		Rec. Rim Width* (in.)	Overall Diameter (in.)	Average Circumference (in.)	Section Width (in.)	Tread Width (in.)	Recommended Rim Type	Weight (lbs.)
--------------	------	------------------	--	-----------------------	------------------------	-----------------------------	---------------------	-------------------	----------------------	---------------

## Competition, Super Comp

	D-2A	D-1	D-6	D-7	D-3						
808-906-081 MATL. NO.	26.0X8.0-15		2119 192100			7.0	26.3	83.0	9.5	7.8	16.1
808-725-081 MATL. NO.	30.0X12.0-15	2112 191798				11.0	30.2	96.0	14.5	12.3	29.4
808-095-081 MATL. NO.	31.0X12.0-15			2585 206637		12.0	30.8	96.5	15.2	12.0	22.6
808-097-081 MATL. NO.	31.0X14.0-15	1999 194375				14.0	31.2	98.0	16.8	14.1	31.1
808-266-081 MATL. NO.	31.5X14.5-15		2121-2 193780			14.0	31.8	100.0	18.2	14.7	34.2
808-163-081 MATL. NO.	32.0X14.5-15	1911 193992				14.0	32.2	101.0	17.7	15.0	34.1
808-921-081 MATL. NO.	33.0X12.0-15			1288-2 23654		12.0	32.4	102.0	16.5	12.3	28.8
808-821-081 MATL. NO.	33.0X13.0-15			# #		12.0	33.0	102.0	17.1	13.3	29.9
808-779-081 MATL. NO.	33.0X14.0-15			2117-2,3 192098		14.0	32.4	102.0	18.3	14.0	30.8
808-164-081 MATL. NO.	33.0X14.5-15		2070 190163			14.0	32.8	104.0	18.9	14.9	34.1
808-942-081 MATL. NO.	33.0X16.0-15		2052 190167			15.0	32.8	102.0	19.6	16.1	38.0
808-942-081 MATL. NO.	33.0X16.0-15	2071 196201				15.0	32.4	104.0	19.9	16.3	39.6
808-031-081 MATL. NO.	33.0X17.0-15		2072 191878			15.0	32.4	104.0	20.5	17.4	39.5
808-801-081 MATL. NO.	33.5X15.0-15		2118-3 192214			14.0	33.5	105.0	17.8	15.1	35.8
808-043-081 MATL. NO.	33.5X17.0-16	2532 208659				16.0	33.8	105.0	21.1	16.8	BEADLOCK 39.1

## Outlaw

	D-4B	D-5							
808-149-081 MATL. NO.	28.0X10.5-15	# #		#	#	#	#	#	#
808-739-081 MATL. NO.	30.0X10.5-15	1790-1 188803		10.0	30.0	94.0	13.0	10.2	31.2

\*Acceptable application for rim width is tread plus or minus one inch  
# - To be announced.

Product Code	Size	Soft To Harder →		Rec. Rim Width* (in.)	Overall Diameter (in.)	Average Circumference (in.)	Section Width (in.)	Tread Width (in.)	Recommended Rim Type	Weight (lbs.)
--------------	------	------------------	--	-----------------------	------------------------	-----------------------------	---------------------	-------------------	----------------------	---------------

## Radial

	D-4B	D-4A	D-4	D-5						
388-717-097 MATL. NO.	30.0X9.0-15	# #			9.0	29.4	92.3	11.6	9.0	22.6
388-717-097 MATL. NO.	30.0X9.0-15	# #		# #	9.0	29.8	93.5	12.0	9.0	22.7
388-250-097 MATL. NO.	31.0X13.5-15		4209 #		14.0	31.7	99.5	16.9	13.8	32.7
388-178-097 MATL. NO.	32.0X14.0-15			6892 198162	14.0	32.2	101.0	17.2	13.8	31.0
388-164-097 MATL. NO.	33.0X14.5-15		4213 #		14.0	33.0	103.8	17.4	14.5	35.0
# MATL. NO.	33.0X17.0-15	# #			#	#	#	#	#	#

# - To be announced.

## Frontrunner® Eagle® Land Speed

- Lightweight design for lower rolling resistance
- Tubeless construction means lightweight performance and less maintenance
- Longer life helps improve cost effectiveness



Eagle Drag Front Runner

Eagle Top Fuel Front Runner

Product Code	Size	Soft To Harder →		Rec. Rim Width* (in.)	Overall Diameter (in.)	Average Circumference (in.)	Section Width (in.)	Tread Width (in.)	Recommended Rim Type	Weight (lbs.)
--------------	------	------------------	--	-----------------------	------------------------	-----------------------------	---------------------	-------------------	----------------------	---------------

## Frontrunner

	HARD								
808-243-089 MATL. NO.	23.0X5.0-15	1961 189891		4.0	23.0	72.7	6.8	5.0	12.2
808-730-089 MATL. NO.	24.0X5.0-15	1962 189955		4.0	24.0	75.8	6.8	5.0	11.3
808-028-089 MATL. NO.	25.0X4.5-15	2981 23505		4.0	25.0	78.5	6.5	4.5	11.6
808-062-089 MATL. NO.	26.0X4.5-15	1964 190130		4.0	26.0	81.2	6.3	4.5	10.8
808-181-089 MATL. NO.	27.0X4.5-15	1965 197495		4.0	27.0	84.8	7.9	4.5	13.5
808-729-089 MATL. NO.	28.0X4.5-15	1966 189822		4.0	28.0	89.1	7.7	5.1	12.4
808-102-089 MATL. NO.	22.0X2.5-17	1445-9 177193		2.5	22.0	69.9	2.5	1.5	4.5
808-130-089 MATL. NO.	22.0X4.0-17	2404 200268		2.5	22.9	72.0	3.4	3.1	5.2

\*Acceptable application for rim width is tread plus or minus one inch

Product Code	Size	Soft To Harder →				Rec. Rim Width* (in.)	Overall Diameter (in.)	Average Circumference (in.)	Section Width (in.)	Tread Width (in.)	Recommended Rim Type	Weight (lbs.)
--------------	------	------------------	--	--	--	-----------------------	------------------------	-----------------------------	---------------------	-------------------	----------------------	---------------

## Eagle Land Speed

		HARD	LOAD LBS.	PSI LBS.	MAX MPH						
808-975-090 MATL. NO.	21.0X5.0-15	2282 #	1200	50	300	4.5	21.3	5.4	4.1		10.0
808-243-090 MATL. NO.	23.0X5.0-15	2283 196199	1700	70	300	4.5	23.1	7.0	5.0		12.0
808-028-090 MATL. NO.	25.0X4.5-15	2284 196198	1700	70	300	4.5	24.8	6.7	4.0		12.0
808-682-089 MATL. NO.	28.0X4.5-15	2286 196215	1700	70	300	4.5	27.8	7.7	4.5		13.0

\*Acceptable application for rim width is tread plus or minus one inch  
# - To be announced.



Listed in order from softest to hardest.  
Note that in some cases, a softer compound is not necessarily more tractive due to continual advances in compound technology.

- D-2** For Pro Mod. Slightly more starting line hook than D-2A.
- D-2A** For Pro Mod, TAD, TAFC, Pro Stock and other high horsepower applications.
- D-2E** For TF/FC and other high horsepower applications.
- D-11** For TAD.
- D-1** For use on Dragsters and other lightweight cars.
- D-9** For use on Motorcycles.
- D-4B** For Stock Eliminator. Slightly more tractive than D-4A.
- D-4A** Good for hot and/or slick track conditions.
- D-4** Excellent wear/longevity for heavy applications, +3,000 lbs.
- D-6** Works well on Dragsters and 1,500 - 2,500-lb. cars.
- D-5** Works well on 2,000 - 3,200-lb. cars.
- D-7** Limited application compound. Can help eliminate shake.
- D-3** For heavier manual and automatic cars, +3,000 lbs.



Soft	Current Compound Selections										Hard	
D2	D-2A	D-2E	D-11	D-1	D-9	D-4B	D-4A	D-4	D-6	D-5	D-7	D-3

- 1 Stiff sidewall
- 2 High growth construction
- 3 Lightweight construction
- 4 Extended tread life construction
- 7 Super Stock automatic application
- 8 "Square Corner" tire profile
- 9 Sportsman Frontrunner with extended tread life





# Eagle® Asphalt Short Track Special

## G-19 Eagle® G-24 Eagle®

- Tread design for responsive steering
- Consistent, repeatable performance for improved cost efficiency
- Compounds enhance tread life
- Stiffer sidewall helps provide strength and toughness



G-19 Eagle      G-24 Eagle

Product Code	Size	Soft To Harder →	Rec. Rim Width* (in.)	Overall Diameter (in.)	Average Circumference (in.)	Section Width (in.)	Tread Width (in.)	Weight (lbs.)
--------------	------	------------------	-----------------------	------------------------	-----------------------------	---------------------	-------------------	---------------

### ASPHALT G-19

	A200	A300	A400	A500							
803-325-159 MATL. NO.	23.5X9.5-13	2818 #			2818	9.0	23.5	74.0	12.0	9.5	15.0
803-240-159 MATL. NO.	26.5X8.0-15		2672 208840		2672	8.0	26.5	83.0	11.0	8.0	20.0
803-241-159 MATL. NO.	27.0X8.0-15		2882 209161		2882	8.0	27.0	85.0	11.0	8.0	20.0
803-251-159 MATL. NO.	26.5X10.0-15		2772 #		2772	10.0	26.5	84.0	11.0	10.0	22.0
803-245-159 MATL. NO.	27.0X10.0-15		2902 #		2902	10.0	27.0	86.0	13.0	10.0	23.0
803-247-159 MATL. NO.	27.0X10.0-15			2925 #	2925	10.0	27.0	86.0	13.0	10.0	23.0

### ASPHALT G-24

	A200	A300	A400								
803-407-159 MATL. NO.	22.0X7.0-13		2714 208574		2714	7.0	22.5	70.0	9.0	7.0	16.0
803-252-159 MATL. NO.	23.0X7.0-13		2716 #		2716	7.0	23.0	72.0	9.0	7.0	16.5
803-893-159 MATL. NO.	22.0X8.0-13	2832 208722			2832	8.0	22.5	70.0	10.0	8.0	17.0
803-673-159 MATL. NO.	23.0X8.0-13	2636 #			2636	8.0	23.0	72.0	11.0	8.0	17.0
803-675-159 MATL. NO.	23.0X8.0-13	2833 209241			2833	8.0	23.0	72.0	11.0	8.0	17.0
803-344-159 MATL. NO.	27.0X7.0-15		2635 208616		2635	6.0	26.5	84.0	9.0	6.0	15.0
803-235-159 MATL. NO.	26.5X8.0-15	2862 208500			2862	8.0	26.5	82.0	11.0	8.0	20.0
803-253-159 MATL. NO.	26.5X8.0-15		2864 208671		2864	8.0	26.5	82.0	11.0	8.0	20.0
803-232-159 MATL. NO.	27.0X8.0-15	2863 208499			2863	8.0	27.0	85.0	11.5	8.0	20.0
803-233-159 MATL. NO.	27.0X8.0-15		2865 208331		2865	8.0	27.0	85.0	11.5	8.0	20.0
803-256-159 MATL. NO.	26.5X10.0-15	2677 208841			2677	10.0	26.0	83.0	13.0	10.0	23.0
803-258-159 MATL. NO.	27.0X10.0-15	2878 209152			2878	10.0	27.0	85.0	13.0	10.0	24.0

10 \*Acceptable application for rim width is tread plus or minus one inch  
# - To be announced.

# Eagle® Dirt Short Track Special

## G-31 Eagle® G-23 Eagle® G-32 Eagle®

- Footprint design promotes even treadwear
- Notched tread elements reduce element feathering
- Contains compounds tailored for dirt applications
- Sidewall design helps resist punctures



G-31 Eagle      G-23 Eagle      G-32 Eagle

Product Code	Size	Soft To Harder →	Rec. Rim Width* (in.)	Overall Diameter (in.)	Average Circumference (in.)	Section Width (in.)	Tread Width (in.)	Weight (lbs.)
--------------	------	------------------	-----------------------	------------------------	-----------------------------	---------------------	-------------------	---------------

### DIRT G-31

	G40	G45	G50	G65	G70							
809-737-846 MATL. NO.	28.0X11.0-15	2325 197645	2377 198013	2326 197646		2325	14.0	28.0	88.0	16.0	12.5	21.0
809-174-846 MATL. NO.	29.0X11.0-15	2328 197642	2378 198012	2329 197643	2457 204091	2328	14.0	29.0	92.0	16.0	12.5	21.0

### DIRT G-23

	G40	G45	G50	G65	G70							
809-417-842 MATL. NO.	27.5X11.0-15	2486 199103				2486	14.0	27.5	86.0	16.0	12.5	20.5
809-416-842 MATL. NO.	27.0X11.0-15	2445 198239				2445	11.0	27.0	84.0	13.5	11.5	20.0
809-418-842 MATL. NO.	27.5X11.0-15	2449 199107				2449	11.0	27.5	86.0	13.5	11.5	20.0
809-450-842 MATL. NO.	22.0X8.0-13	2820 #				2820	8.0	22.0	72.0	10.0	8.5	16.0
809-451-842 MATL. NO.	22.0X8.0-13		2856 #			2856	8.0	22.0	72.0	10.0	8.5	16.0
809-452-842 MATL. NO.	23.0X8.0-13	2821 #				2821	8.0	23.0	74.0	10.0	8.5	16.5
809-453-842 MATL. NO.	23.0X8.0-13		2857 #			2857	8.0	23.0	74.0	10.0	8.5	16.5

### DIRT G-32

	G40	G45	G50	G65	G70							
809-272-848 MATL. NO.	27.0X8.0-15	2945 #				2945	8.0	27.0	84.0	10.7	9.0	19.0
809-270-848 MATL. NO.	27.0X8.0-15			2965 #		2965	8.0	27.0	84.0	10.7	9.0	19.0
809-279-848 MATL. NO.	27.5X8.0-15	2946 #				2946	8.0	27.5	87.0	10.7	9.0	19.5
809-273-848 MATL. NO.	27.5X8.0-15			2966 #		2966	8.0	27.5	87.0	10.7	9.0	19.5

\*Acceptable application for rim width is tread plus or minus one inch  
# - To be announced. Independent dealers must establish their own retail prices.

For current suggested retail prices, visit [www.racegoodyear.com](http://www.racegoodyear.com)

# Eagle® Dirt Track Special

## G-16 Eagle®

- For sprint front applications
- Footprint and contact patch offer enhanced performance
- Sidewall enhances steering response

## G-25 Eagle®

- Tread design promotes even wear
- Notched tread elements reduce element feathering
- Wide grooves enhance self-cleaning action



G-25 Eagle      G-16 Eagle

Product Code	Size	Soft To Harder →					Rec. Rim Width* (in.)	Overall Diameter (in.)	Average Circumference (in.)	Section Width (in.)	Tread Width (in.)	Weight (lbs.)
--------------	------	------------------	--	--	--	--	-----------------------	------------------------	-----------------------------	---------------------	-------------------	---------------

### Sprint

		050	100	200	300	400						
812-067-086	84/8.0-15		2591	2592		2594	8.00	26.7	84.0	10.8	8.0	14.6
MATL. NO.	(G-16)		206539	206540		206551						
812-069-086	87/15.0-15	2700	2701				15.00	27.7	87.0	18.4	15.0	27.0
MATL. NO.	(G-25)	206552	206553									
812-072-086	89/15.0-15	2710	2711				15.00	28.3	89.0	18.3	15.0	27.0
MATL. NO.	(G-25)	206554	206555									
812-074-086	91/15.0-15	2720	2721	2722			15.00	29.0	91.0	18.2	15.0	27.5
MATL. NO.	(G-25)	206556	206557	206558								
812-075-086	93/15.0-15	2730	2731	2732	2733		15.00	29.6	93.0	18.2	15.0	28.0
MATL. NO.	(G-25)	206559	206560	206561	206562							
812-076-086	95/15.0-15	2740	2741	2742	2743		15.00	30.2	95.0	17.9	15.0	28.5
MATL. NO.	(G-25)	206563	206564	206565	206566							
812-079-086	97/15.0-15	2750	2751	2752	2753		15.00	31.2	97.0	17.9	15.0	29.0
MATL. NO.	(G-25)	206444	206445	206446	206447							
812-083-086	105/17.0-15	2800	2801	2802	2803	2804	18.00	33.4	105.0	21.8	18.0	34.0
MATL. NO.	(G-25)	206567	206568	206569	206570	206571						

\*Acceptable application for rim width is tread plus or minus one inch

# Eagle® Dirt Track Special

## G-15 Eagle®

- Economy front tire



G-15 Eagle

Product Code	Size	Soft To Harder →					Rec. Rim Width* (in.)	Overall Diameter (in.)	Average Circumference (in.)	Section Width (in.)	Tread Width (in.)	Weight (lbs.)
--------------	------	------------------	--	--	--	--	-----------------------	------------------------	-----------------------------	---------------------	-------------------	---------------

### Econo Sprint

		M20											
812-078-086	26.5X8.0-15					2250	8.00	26.7	84.0	11.3	8.0	14.6	
MATL. NO.	(G-15)						198575						

## Pike's Peak

- Proven performance in Pike's Peak competition
- Tread enhances traction on both dirt and asphalt surfaces
- Tread compound helps promote traction in both wet and dry conditions



Pike's Peak

Product Code	Size	Soft To Harder →					Rec. Rim Width* (in.)	Overall Diameter (in.)	Average Circumference (in.)	Section Width (in.)	Tread Width (in.)	Weight (lbs.)
--------------	------	------------------	--	--	--	--	-----------------------	------------------------	-----------------------------	---------------------	-------------------	---------------

### Pike's Peak

		M15(WIDE)											
811-244-073	29.5X11.5-15W					1923	10.00	29.0	91.0	12.5	11.1	31.5	
MATL. NO.							23776						

\*Acceptable application for rim width is tread plus or minus one inch

# Eagle® Dirt Track Special

## G-3 Motorcycle DT II™

- Responsive cornering and handling
- The selection of compounds offers traction and toughness, from short tracks to mile tracks



G-3 Motorcycle DT II

Product Code	Size	Soft To Harder →	Rec. Rim Width* (in.)	Overall Diameter (in.)	Average Circumference (in.)	Section Width (in.)	Tread Width (in.)	Weight (lbs.)
--------------	------	------------------	-----------------------	------------------------	-----------------------------	---------------------	-------------------	---------------

### Motorcycle DT II

		CD2	CD5	CD8						
811-033-915	27.0X7.0-19	2536	3616		2.80	26.8	84.0	5.1	7.0	11.0
MATL. NO.	(G3)	203953	23748							
811-860-915	27.5X7.5-19	2537	1657	1637	3.50	27.7	87.0	5.7	7.5	12.0
MATL. NO.	(G3)	203954	23825	23824						

\*Acceptable application for rim width is tread plus or minus one inch

# Eagle® Sports Car Special

## G-19 Eagle®

- Premium asphalt tire
- Smooth tread design for increased steering response
- Consistent, repeatable performance for improved cost efficiency
- Compounds enhance tread life
- R475 compound for front-wheel drive cars



G-19 Eagle

Product Code	Size	Soft To Harder →	Rec. Rim Width* (in.)	Overall Diameter (in.)	Section Width (in.)	Tread Width (in.)	Weight (lbs.)
--------------	------	------------------	-----------------------	------------------------	---------------------	-------------------	---------------

### GT & Production Classes

		R175	R250	R430	R475	R600					
807-434-068	20.0X8.0-13	1704	2169	1705	1940		6.0	20.1	9.1	8.0	13.0
MATL. NO.		190754	193081	186806	190591						
807-685-068	20.0X9.5-13		1709	1711	1942		7.0	19.9	10.2	9.2	14.2
MATL. NO.			186808	186809	190592						
807-486-068	21.0X10.0-13				1726		7.0	21.0	10.2	9.7	16.0
MATL. NO.					186807						
807-889-068	23.0X8.0-15		1772	1774			7.0	22.6	10.0	8.4	16.3
MATL. NO.			186830	188614							
807-409-104	23.0X9.0-15		2069	1782	1873	1783	7.0	23.0	10.4	9.3	18.0
MATL. NO.			192563	187256	190097	188512					

### Sports GT

		R250	R430	R475	R600					
807-493-068	25.0X11.0-15			1955		10.0	25.3	12.2	10.5	24.0
MATL. NO.				190756						
807-674-059	27.0X11.0-15			1956		10.0	26.8	13.3	10.9	22.1
MATL. NO.				190695						
807-220-068	23.5X10.5-16		1651			11.0	23.3	11.8	10.1	18.0
MATL. NO.			23334							
807-939-068	23.5X11.5-16		2154	1653		11.0	23.8	11.6	10.6	19.0
MATL. NO.			193117	23477						
807-320-068	25.0X12.0-16			1660	1661	12.0	24.6	13.5	1.7	21.0
MATL. NO.				23356	23357					
807-322-068	25.0X13.0-16		1980	1570		12.0	24.5	13.7	12.4	22.5
MATL. NO.			190533	184222						
807-764-068	27.0X14.0-16		1981	1571		14.0	26.6	15.9	13.7	26.5
MATL. NO.			190535	184247						

### Pro-Mazda

		R340									
807-293-068	21.0X8.0-13	2597					9.0	21.2	9.9	8.1	11.2
MATL. NO.		204583									
807-136-068	22.0X11.0-13	2598					11.0	22.5	12.6	10.7	14.5
MATL. NO.		204446									

\*Acceptable application for rim width is tread plus or minus one inch



# Eagle® Sports Car Special

## G-19 Formula Eagle®

- A 21" tall Formula Ford and Formula Continental for quick turn-in response
- Radial tires in GT1 and Formula Atlantic
- Dry cornering, traction and stability
- Large selection of compounds for different track conditions
- Great handling and traction
- Quick steering response



G-19 Formula Eagle

# Eagle® Sports Car Special

## Spec Racer Ford

- Compounded for excellent traction and long wear
- Construction only for Spec Racer Ford



Spec Racer Ford

Spec Racer Ford Wet

Product Code	Size	Dry	Rain	Rec. Rim Width* (in.)	Overall Diameter (in.)	Section Width (in.)	Tread Width (in.)	Weight (lbs.)
--------------	------	-----	------	-----------------------	------------------------	---------------------	-------------------	---------------

### Formula

Product Code	Size	Dry	Rain	Rec. Rim Width* (in.)	Overall Diameter (in.)	Section Width (in.)	Tread Width (in.)	Weight (lbs.)
		R100	R160	R175	R250	R420	R430	R475
807-366-068 MATL. NO.	20.0X6.0-13 F/F							
				5.5	20.6	7.3	6.2	10.0
807-089-068 MATL. NO.	20.0X6.5-13 F/F				2273 193352			2538 204594
				6.0	20.5	7.7	6.4	8.5
807-274-068 MATL. NO.	22.5X7.5-13 F/F				1671 186757			2539 204595
				5.5	22.4	10.2	7.4	15.2
807-299-068 MATL. NO.	20.0X7.0-13 FC/S2000 FM				1586 184528			1578 184221
				6.0-8.0	20.5	8.7	7.2	10.0
807-434-068 MATL. NO.	20.0X8.0-13 CSR FM				1763 188513	1995 190748		2499 204958
				8.0	20.0	9.1	7.7	11.0
807-135-068 MATL. NO.	22.0X10.0-13 CSR FM				1764 188511	1996 190746		2500 204955
				10.0	22.3	11.7	9.8	14.0
807-961-068 MATL. NO.	20.0X9.5-13 F/ATL				3372 129769			1951 190697
				10.0	20.3	10.9	9.1	9.5
807-684-068 MATL. NO.	22.0X9.0-13 F/ATL - FM FC/S2000				2104 193109			1579 184287
				8.0-10.0	22.5	11.3	9.2	14.4
807-915-068 MATL. NO.	23.0X13.0-13 F/ATL					1953 190696		
				14.0	23.0	16.1	12.3	20.0
807-403-068 MATL. NO.	21.0X5.5-15 F/V							#
				4.0	21.5	5.8	5.0	9.3
807-975-068 MATL. NO.	21.0X5.0-15 F/V							#
				4.0	21.5	5.2	4.3	9.0
807-199-068 MATL. NO.	22.5X5.5-15 F/V							#
				4.0	22.3	6.2	5.2	10.1
807-480-068 MATL. NO.	21.0X7.0-13 F/C, F/F				2209 194826			
				6.0	21.5	8.1	7.2	11.0

Product Code	Size	Dry	Rain	Rec. Rim Width* (in.)	Overall Diameter (in.)	Section Width (in.)	Tread Width (in.)	Weight (lbs.)
--------------	------	-----	------	-----------------------	------------------------	---------------------	-------------------	---------------

### Spec Racer Ford

807-189-068 MATL. NO.	22.0X7.0-13	FRONT	2525 199605	5.5	21.9	8.8	7.1	17.5
807-189-068 MATL. NO.	22.0X7.0-13	REAR	2525 199605	7.0	21.8	9.4	7.1	17.5
807-189-096 MATL. NO.	22.0X7.0-13	FRONT	2624 203952	5.5	22.4	8.8	7.1	16.0
807-189-096 MATL. NO.	22.0X7.0-13	REAR	2624 203952	7.0	22.3	9.4	7.1	16.0

\*Acceptable application for rim width is tread plus or minus one inch

Product Code	Size	Dry	Rain	Rec. Rim Width* (in.)	Overall Diameter (in.)	Section Width (in.)	Tread Width (in.)	Weight (lbs.)
--------------	------	-----	------	-----------------------	------------------------	---------------------	-------------------	---------------

### Formula SAE

807-299-068 MATL. NO.	20.0X7.0-13	2692 200904		6.0-8.0	20.5	8.7	7.2	10.0
807-299-096 MATL. NO.	20.0X7.0-13	2691 204480		6.0-8.0	20.5	8.7	7.2	8.5

\*Acceptable application for rim width is tread plus or minus one inch  
# - To be announced.

# Eagle® Sports Car Special – Rain

## G-18 Eagle F-1 Eagle

- Open tread pattern for full wet conditions
- Intermediate patterns for damp, drying conditions
- Compounds available for all classes



G-18 Eagle

F-1 Eagle

Product Code	Size	Soft To Harder →	Rec. Rim Width* (in.)	Overall Diameter (in.)	Section Width (in.)	Tread Width (in.)	Weight (lbs.)
--------------	------	------------------	-----------------------	------------------------	---------------------	-------------------	---------------

### Formula – Rain

			G-18 R065	G-18 R085	F1 R085I					
807-089-096 MATL. NO.	20.0X6.5-13	F/F - S2 F/C - F/M	1883 190095			6.0	21.0	7.7	5.9	10.5
807-434-096 MATL. NO.	20.0X8.0-13	CSR - F/M		2840 173493		8.0	19.5	9.3	7.7	10.5
807-135-096 MATL. NO.	22.0X10.0-13	CSR - F/M		2841 173494		10.0	22.3	12.0	9.6	13.0
807-684-096 MATL. NO.	22.0X9.0-13	S2 F/C - F/M	1318 172771			9.0	22.4	11.1	8.8	13.0
807-502-096 MATL. NO.	22.5X7.5-13	F/F	1319 172775			5.5	22.7	8.9	7.7	13.5
807-403-068 MATL. NO.	21.0X5.5-15	F/V	1481 189898			4.0	21.5	5.8	5.0	9.3
807-601-096 MATL. NO.	23.0X5.0-15	F/V		3000 200107		4.0	23.0	6.2	5.0	7.0

### Production & GT Rain

807-743-096 MATL. NO.	20.5X7.5-13	GT			1079 156439	6.0	21.5	8.0	7.0	11.0
807-889-096 MATL. NO.	23.0X8.0-15	GT			1275 169809	7.0	22.6	10.0	8.4	17.0
807-137-096 MATL. NO.	23.0X10.5-16	GT		2258 193031		11.0	23.1	11.5	10.1	16.5
807-997-096 MATL. NO.	25.0X12.0-16	GT		1446 181527		12.0	25.1	13.2	11.1	18.5
807-937-096 MATL. NO.	27.0X12.0-16	GT		1447 181252		12.0	26.3	14.2	12.4	22.5

\*Acceptable application for rim width is tread plus or minus one inch

# Vintage Sports Car Special



G-12 Blue Streak

G-7 Blue Streak

G-19 Eagle

G-12A Blue Streak

Product Code	Size	Soft To Harder →	Rec. Rim Width* (in.)	Overall Diameter (in.)	Section Width (in.)	Tread Width (in.)	Weight (lbs.)
--------------	------	------------------	-----------------------	------------------------	---------------------	-------------------	---------------

### Blue Streak Special & Can-Am

			R250	R430	R655	FIRM					
807-051-068 MATL. NO.	5.50-15	G-12				3083 109086	5.0	25.5	8.5	6.6	14.5
807-051-068 MATL. NO.	5.50-15	G-7			3328 129830		6.0	22.8	7.5	6.4	12.0
807-052-068 MATL. NO.	6.00-15	G-7		3418 134404	1724 187964	1725 188102	8.0	25.5	10.6	8.4	17.0
807-073-068 MATL. NO.	26.5X8.0-15	COBRA			2546 121183		8.0	26.5	11.0	7.9	17.8
807-481-068 MATL. NO.	26.5X10.0-15	COBRA			2547 23417		10.0	27.0	12.9	10.2	22.3
807-118-068 MATL. NO.	7.00-15	G-7			1756 188026	1757 188103	9.0	26.8	12.0	8.7	18.7
807-289-068 MATL. NO.	8.00-15	G-7			1758 188182	1759 188250	10.0	26.8	13.1	10.1	19.7
807-410-068 MATL. NO.	23.0X10.5-15	G-19	2225 192788	2415 23386			10.0	23.4	11.8	10.4	16.9
807-048-068 MATL. NO.	27.0X14.0-15	G-19	2226 192787	2416 23286			17.0	27.0	18.5	14.8	15.3

### Vintage Indy

387-321-097 MATL. NO.	25.5X10.5-15	G-19			6538 183541		10.0	25.7	11.6	10.4	20.0
387-682-097 MATL. NO.	28.0X14.0-15	G-19			6535 183243		14.0	28.0	16.0	14.0	23.5

### Vintage Stock Car

813-674-059 MATL. NO.	27.0X11.0-15	G-19				1372 181174	9.5	27.0	11.8	11.0	25.5
--------------------------	--------------	------	--	--	--	----------------	-----	------	------	------	------

\*Acceptable application for rim width is tread plus or minus one inch



# Eagle® Sports Car Radial

## G-19 Eagle®

- Premium asphalt tire
- Smooth tread design for increased steering response
- Consistent, repeatable performance for improved cost efficiency
- Compounds enhance tread life



G-19 Eagle

# Eagle® Sports Car Radial – Rain

## G-18 Eagle®

- Open tread pattern for full wet conditions
- Intermediate patterns for damp, drying conditions
- Compounds available for all classes



G-18 Eagle

Product Code	Size	Soft To Harder →	Rec. Rim Width* (in.)	Overall Diameter (in.)	Section Width (in.)	Tread Width (in.)	Weight (lbs.)
--------------	------	------------------	-----------------------	------------------------	---------------------	-------------------	---------------

### Sports Car Radial

	G-19	R160	R210	R250	R370	R377	R430	R475	
387-236-097 MATL. NO.	23.5X10.5-16 GT		5875 80773				5876 80774		10.0 23.5 11.2 10.6 18.0
387-112-097 MATL. NO.	25.5X12.0-16 GT		5880 80758						12.0 25.5 13.5 12.2 24.5
387-168-097 MATL. NO.	25.5X14.0-16 GT		5886 80764				5887 80765		14.0 25.4 15.2 14.0 24.5
387-206-097 MATL. NO.	27.0X13.0-16 GT		5889 80768				5890 80769		12.0 27.0 14.4 12.9 26.5
387-205-097 MATL. NO.	25.5X12.0-17 GT			#	#		6438 174939		13.0 25.5 13.7 12.2 23.0
387-348-097 MATL. NO.	28.5X14.5-17 GT			#	#		6442 174969		14.5 28.5 15.9 14.6 29.5
387-110-097 MATL. NO.	25.5X12.0-16 GT1						6731 192782		12.0 25.5 13.5 12.2 24.5
387-120-097 MATL. NO.	27.0X13.0-16 GT1						6732 192785		12.0 27.0 14.4 12.9 26.5
387-313-097 MATL. NO.	25.5X12.0-18 GT			6996 204552					12.0 25.6 13.1 12.1 23.9
387-011-097 MATL. NO.	25.5X12.5-18 GT					6531 183208			13.5 25.6 14.2 12.4 22.9
387-349-097 MATL. NO.	28.5X14.5-18 GT					6402 172543			14.5 28.5 15.9 14.8 24.0
387-442-097 MATL. NO.	25.0X10.0-18 GT			6993 204439					10.5 25.0 11.2 10.0 18.9
387-160-097 MATL. NO.	25.5X14.0-16 GT1			6896 198508	6953 201396				12.0 25.5 14.1 14.0 25.0
387-132-097 MATL. NO.	28.5X14.5-16 GT1			6898 198505	6954 201395				13.0 28.5 15.4 14.8 28.5
387-301-097 MATL. NO.	23.0X9.5-15 FA	#							10.0 22.9 10.7 9.7 16.0
387-302-097 MATL. NO.	23.5X11.0-15 FA	#							14.0 23.7 14.0 11.7 20.5
387-063-097 MATL. NO.	21.5X8.0-13 FM			4199 207527			4191 207119		9.0 21.6 9.8 8.2 13.2
387-061-097 MATL. NO.	22.5X11.0-13 FM			4200 207610			4192 207115		11.0 22.6 12.2 10.6 16.4

\*Acceptable application for rim width is tread plus or minus one inch  
# - To be announced.

Product Code	Size	Soft To Harder →	Rec. Rim Width* (in.)	Overall Diameter (in.)	Section Width (in.)	Tread Width (in.)	Weight (lbs.)
--------------	------	------------------	-----------------------	------------------------	---------------------	-------------------	---------------

### Sports Car Radial Rain

			R065	R080	R085		
387-236-097 MATL. NO.	23.5X10.5-16 GT		6756 194838	6416 174161			10.0 23.5 11.2 10.6 23.5
387-112-097 MATL. NO.	25.5X12.0-16 GT		6757 194836		#	#	12.0 25.5 13.4 12.5 24.5
387-168-097 MATL. NO.	25.5X14.0-16 GT				6991	#	14.0 25.5 15.0 13.9 26.0
387-206-097 MATL. NO.	27.0X13.0-16 GT				#	#	13.0 27.1 14.7 13.3 26.5
387-205-097 MATL. NO.	25.5X12.0-17 GT				4162	#	13.0 25.5 13.6 12.5 23.5
387-348-097 MATL. NO.	28.5X14.5-17 GT				4163	#	14.5 28.5 15.9 14.6 24.0
387-160-097 MATL. NO.	25.5X14.0-16 GT1				6672 206848		12.0 25.5 14.1 14.0 30.0
387-132-097 MATL. NO.	28.5X14.5-16 GT1				6673 206847		13.0 28.5 15.4 14.8 36.6
387-063-097 MATL. NO.	21.5X8.0-13 FM				4193 207120		9.0 21.6 9.8 8.2 15.1
387-061-097 MATL. NO.	22.5X11.0-13 FM				4194 207116		11.0 22.6 12.2 10.6 19.0

\*Acceptable application for rim width is tread plus or minus one inch  
# - To be announced.

# Notes

# Notes

