

Eagle Dragway Special

- Large selection of sizes, compounds and constructions for all applications
- Little break-in required
- Long-lasting to help lower tire expenses
- Proven performance over a wide range of track conditions



Size	Tire Code	Compound	Comments	MSRP	Rim Width	Overall Diam	Avg Circumference	Section Width	Tread Width	Weight
------	-----------	----------	----------	------	-----------	--------------	-------------------	---------------	-------------	--------

Top Fuel & Funny Car

36.0x17.5-16	2681	D-2F	HG,BL	\$767	16.0	36.6	115.0	21.6	17.3	49.1
--------------	------	------	-------	-------	------	------	-------	------	------	------

Pro Mod, Alcohol

34.5x17.0-16	1022	D-2A	LW,BL	\$464	16.0	34.7	109.0	21.0	17.0	42.1
36.0x17.0-16	1230	D-2A	HG,BL	\$545	16.0	36.3	114.0	21.4	17.0	49.9
36.0x17.0-16	2540	D-11	HG,BL	\$545	16.0	36.3	114.0	21.4	17.0	46.8

Pro Stock, Super Gas

32.0x14.0-15	1160	D-1	LW,MS	\$341	14.0	32.5	102.0	17.0	14.4	34.2
32.0x14.0-15	1984	D-5	MS	\$343	14.0	32.1	101.0	17.0	14.4	39.3
32.0x14.5-15	1672	D-5	MS	\$344	14.0	32.8	103.0	17.7	14.8	39.4
32.0x16.0-15	2252	D-1	LW,MS	\$346	15.0	32.5	102.0	18.4	16.0	35.3
32.0x16.0-15	1408	D-5	MS	\$346	15.0	32.5	102.0	18.4	16.0	39.6
32.5x17.0-15	2051	D-4A	LW,SS	\$399	15.0	31.8	100.0	20.8	17.2	41.1
33.0x15.0-15	2078	D-5	MS	\$348	14.0	33.1	104.0	17.5	15.0	40.6
33.0x16.0-15	2052	D-6		\$357	15.0	32.5	102.0	19.6	16.1	38.0
33.0x17.0-15	2556	D-6	SS	\$399	16.0	32.5	102.0	20.5	17.3	41.0
33.0x17.0-15	2053	D-4A	SS	\$399	15.0	32.5	102.0	20.6	17.3	42.9
33.5x15.0-15	2079	D-5	MS	\$350	14.0	33.7	106.0	17.8	15.1	39.2
33.5x17.0-16	2200	D-4A	SS,BL	\$542	16.0	33.4	105.0	20.8	17.4	43.1
33.5x17.0-16	2532	D-2A	BL	\$407	16.0	33.4	105.0	21.1	16.8	39.1
34.5x17.0-16	1022	D-2A	LW,BL	\$464	16.0	34.7	109.0	21.0	17.0	42.1

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall
ET - Extended tread life, **MC** - Motorcycle front, **BL** - Beadlock wheel required

Size	Tire Code	Compound	Comments	MSRP	Rim Width	Overall Diam	Avg Circumference	Section Width	Tread Width	Weight
Stock, Super Stock										
28.0x9.0-15	2790	D-5		\$181	8.0	28.0	88.0	10.7	9.0	21.3
28.0x10.0-15	2791	D-5		\$185	10.0	28.0	88.0	12.0	10.0	23.1
28.0x10.5-15	2892	D-5		\$198	10.0	28.0	88.0	12.5	10.5	24.4
29.0x9.0-15	2793	D-5		\$196	8.0	29.0	91.0	10.9	9.0	21.0
29.0x10.0-15	2794	D-5		\$203	10.0	29.0	91.0	11.8	10.0	23.0
29.0x11.0-15	2796	D-5		\$219	10.0	29.0	91.0	12.8	10.9	25.1
29.0x12.0-15	2797	D-5		\$224	11.0	29.0	91.0	13.0	11.8	26.3
29.5x10.5-15	2709	D-5		\$270	10.0	29.9	94.0	13.0	10.2	27.6
30.0x9.0-15	1909	D-5		\$246	8.0	30.7	96.5	12.4	9.0	25.0
30.0x9.0-15	4450	D-8	R,LW	\$235	9.0	29.4	92.3	11.6	9.0	22.6
30.0x9.0-15	4451	D-8	R,LW	\$235	9.0	29.9	94.0	12.0	9.0	22.7
30.0x11.5-15	2016	D-5		\$279	10.0	29.9	94.0	13.8	11.4	29.0
30.0x12.5-15	2017	D-5		\$290	12.0	30.2	95.0	15.2	12.4	30.2
31.0x13.0-15	2018	D-5	MS	\$321	12.0	30.6	96.0	15.6	12.8	33.4
31.0x14.0-15	1999	D-1		\$321	14.0	31.2	98.0	16.8	14.1	31.1
31.0x14.0-15	2019	D-5	MS	\$324	12.0	30.9	97.0	16.2	14.0	35.8
31.5x14.5-15	2121	D-6	HG	\$328	14.0	31.8	100.0	18.2	14.7	34.2
31.5x14.5-15	1823	D-4A		\$331	14.0	31.8	100.0	18.2	14.7	34.1
33.0x14.0-15	1831	D-4A	HG	\$340	14.0	32.5	102.0	18.2	14.0	34.9
33.0x14.5-15	2070	D-6		\$336	14.0	33.1	104.0	18.9	14.9	34.1

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall
ET - Extended tread life, **MC** - Motorcycle front, **BL** - Beadlock wheel required

Size	Tire Code	Compound	Comments	MSRP	Rim Width	Overall Diam	Avg Circumference	Section Width	Tread Width	Weight
Competition Eliminator, Super Comp										
26.0x8.0-15	2119	D-6		\$222	7.0	26.4	83.0	9.5	7.8	16.1
30.0x12.0-15	2112	D-1		\$289	11.0	30.6	96.0	14.5	12.3	29.4
31.0x12.0-15	2585	D-3	HG,LW	\$299	12.0	30.7	96.5	15.2	12.0	22.6
31.0x14.0-15	1999	D-1		\$321	14.0	31.2	98.0	16.8	14.1	31.1
31.5x14.5-15	2121	D-6	HG	\$328	14.0	31.8	100.0	18.2	14.7	34.2
32.0x14.5-15	1911	D-1		\$342	14.0	32.1	101.0	17.7	15.0	34.1
32.5x17.0-15	2051	D-4A	LW,SS	\$399	15.0	31.8	100.0	20.8	17.2	41.1
33.0x12.0-15	1288	D-7	HG	\$333	12.0	32.5	102.0	16.5	12.3	28.8
33.0x14.0-15	2117	D-7	HG,LW	\$336	14.0	32.5	102.0	18.3	14.0	30.8
33.0x14.5-15	2070	D-6		\$336	14.0	33.1	104.0	18.9	14.9	34.1
33.0x16.0-15	2533	D-2A		\$325	15.0	33.7	106.0	20.2	16.5	40.5
33.0x17.0-15	2534	D-2A		\$335	16.0	33.7	106.0	21.2	17.5	41.2
33.0x17.0-15	2556	D-6	SS	\$399	16.0	32.5	102.0	20.5	17.3	41.0
33.0x17.0-15	2053	D-4A	SS	\$399	15.0	32.5	102.0	20.6	17.3	42.9
33.0x17.0-16	2674	D-2A	BL	\$402	16.0	32.6	102.5	21.1	16.9	39.1
33.5x15.0-15	2118	D-6	LW	\$353	14.0	33.4	105.0	17.8	15.1	35.8
33.5x17.0-16	2532	D-2A	BL	\$407	16.0	33.4	105.0	21.1	16.8	39.1
33.5x17.0-16	2200	D-4A	SS,BL	\$542	16.0	33.4	105.0	20.8	17.4	43.1
34.5x17.0-16	1022	D-2A	LW,BL	\$464	16.0	34.7	109.0	21.0	17.0	42.1

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall
ET - Extended tread life, **MC** - Motorcycle front, **BL** - Beadlock wheel required

Size	Tire Code	Compound	Comments	MSRP	Rim Width	Overall Diam	Avg Circumference	Section Width	Tread Width	Weight
------	-----------	----------	----------	------	-----------	--------------	-------------------	---------------	-------------	--------

Eagle Drag Radial

30.0x9.0-15	4450	D-8	R,LW	\$235	9.0	29.4	92.3	11.6	9.0	22.6
30.0x9.0-15	4451	D-8	R,LW	\$235	9.0	29.8	94.0	12.0	9.0	22.7
31.0x13.5-15	4459	D-8	R	\$320	14.0	31.7	99.5	16.9	13.8	32.7
32.0x14.0-15	4461	D-8	R	\$356	14.0	32.1	101.0	17.2	13.8	31.0
33.0x14.5-15	4463	D-8	R	\$377	14.0	33.0	103.8	17.4	14.5	35.0
30.0x10.5-15	4465	D-8	R	\$252	10.0	29.6	93.0	13.25	10.5	23.5

Outlaw 8.5 & 10.5

26.0x8.5-15	2619	D-2A		\$187	9.0	26.6	83.5	10.5	8.9	17.7
28.0x10.5-15	2892	D-5		\$198	10.0	28.0	88.0	12.5	10.5	24.4
28.0x10.5-15	2899	D-8A	SS	\$249	10.0	28.0	88.0	12.1	10.3	25.7
29.5x10.5-15	2690	D-4B	SS	\$273	10.0	29.9	94.0	13.0	10.2	31.2
29.5x10.5-15	2709	D-5		\$270	10.0	29.9	94.0	13.0	10.2	27.6
33.0x10.5-16	TBD	TBD	SS	-	TBD	TBD	TBD	TBD	TBD	TBD

Motorcycle

25.0x5.5-18	2084	D-3	SQ	\$200	5.0	25.5	80.0	6.1	5.3	9.7
25.0x7.0-18	2980	D-6	SQ	\$203	6.0	25.5	80.0	7.0	6.6	11.3
25.0x7.0-18	2982	D-3	SQ	\$203	6.0	25.5	80.0	7.0	6.6	11.3
28.0x9.0-15	2790	D-5		\$181	8.0	28.0	88.0	10.7	9.0	21.3
28.0x10.0-15	2791	D-5		\$185	10.0	28.0	88.0	12.0	10.0	23.1
28.0x10.5-15	2892	D-5		\$198	10.0	28.0	88.0	12.5	10.5	24.4
31.0x13.0-15	2018	D-5	MS	\$321	12.0	30.6	96.0	15.6	12.8	33.4
31.0x14.0-15	2019	D-5	MS	\$324	12.0	30.9	97.0	16.2	14.0	35.8

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall
ET - Extended tread life, **MC** - Motorcycle front, **BL** - Beadlock wheel required

Size	Tire Code	Compound	Comments	MSRP	Rim Width	Overall Diam	Avg Circumference	Section Width	Tread Width	Weight
Frontrunner										
22.0x2.5-17	1445	Hard	ET	\$149	2.5	22.2	69.9	2.5	1.5	4.5
22.0x4.0-17	2904	Hard		\$220	2.5	22.9	72.0	3.4	3.1	5.2
23.0x5.0-15	1961	Hard		\$192	4.0	23.1	72.7	6.8	5.0	12.2
23.5x4.5-18	2322	Hard	MC	\$181	2.5	23.4	73.5	3.3	4.3	5.1
24.0x5.0-15	1962	Hard		\$156	4.0	24.1	75.8	6.8	5.0	11.3
25.0x4.5-15	2991	Hard	LW	\$159	4.0	25.3	79.5	6.5	4.5	9.8
26.0x4.5-15	1964	Hard		\$161	4.0	25.8	81.2	6.3	4.5	10.8
26.0x4.5-17	TBD	Hard			4.0					
27.0x4.5-15	1965	Hard		\$162	4.0	27.0	84.8	7.9	4.5	13.5
28.0x4.5-15	1966	Hard		\$164	4.0	28.4	89.1	7.7	5.1	12.4

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall
ET - Extended tread life, **MC** - Motorcycle front, **BL** - Beadlock wheel required

Eagle SS DOT Radial

- DOT approved
- Intended for racetrack use only
- Tread compound designed specifically for DOT Drag applications
- Unique sidewall stylene



Size	Tire Code	Compound	Comments	MSRP	Rim Width	Overall Diam	Section Width	Tread Width	Weight
------	-----------	----------	----------	------	-----------	--------------	---------------	-------------	--------

Eagle SS DOT Radial

P235/60R15	4300	DOT	R	\$182	7.0	26.0	8.3	21.8	21.8
P275/50R15	4301	DOT	R	\$187	8.5	26.0	11.0	10.2	26.4
P275/60R15	4305	DOT	R	\$199	8.0	28.0	11.2	9.5	25.7
P325/50R15	4306	DOT	R	\$217	10.0	28.0	13.8	11.5	29.3
P295/65R15	4307	DOT	R	\$215	8.5	30.1	12.3	10.5	31.8
P315/60R15	4308	DOT	R	\$215	9.5	30.1	13.0	11.5	33.2
P255/50R16	4302	DOT	R	\$199	8.0	26.1	10.3	9.4	24.2
P315/35R17	4304	DOT	R	\$220	11.0	25.8	12.5	11.6	27.6
P275/40R17	4303	DOT	R	\$217	9.5	26.0	10.8	10.0	26.4

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall
ET - Extended tread life, **MC** - Motorcycle front, **BL** - Beadlock wheel required

Eagle Land Speed

- Lightweight design for lower rolling resistance
- Tubeless construction means lightweight performamnce and less maintenance
- Longer life helps improve cost effectiveness

Size	Tire Code	Compound	MSRP	Rim Width	Overall Diam	Section Width	Tread Width	Weight	Min Inflation (psi)	Max Load (lbs)	Max Speed (MPH)
------	-----------	----------	------	-----------	--------------	---------------	-------------	--------	---------------------	----------------	-----------------

Eagle Land Speed

21.0x5.0-15	2282	Hard	\$535	4.5	21.3	5.4	4.1	10.0	50.0	1200	300
23.0x5.0-15	2283	Hard	\$555	4.5	23.1	7.0	5.0	12.0	70.0	1700	300
25.0x4.5-15	2284	Hard	\$561	4.5	24.8	6.7	4.0	12.0	70.0	1700	300
28.0x4.5-15	2286	Hard	\$585	4.5	27.8	7.7	4.5	13.0	70.0	1700	300
28.0x10.0-15	2270	Hard	\$229	9.0	28.0	13.2	10.3	22.0	70.0	1700	300

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall
ET - Extended tread life, **MC** - Motorcycle front, **BL** - Beadlock wheel required