

Tire Code	MSRP	Tire Size	Compound	Comments	Rim Width	Overall Diam	Avg Circumference	Section Width	Tread Width	Weight
-----------	------	-----------	----------	----------	-----------	--------------	-------------------	---------------	-------------	--------

Top Fuel & Funny Car

2747	\$899	36.0x17.5x16	D-2H	BL, LW	16	36.6	115	21.8	17.3	48.0
------	-------	--------------	------	--------	----	------	-----	------	------	------

Pro Mod, Alcohol

3122	\$535	34.5x17.0x16	D-2G		16	34.8	109	21.3	17.0	43.0
3036	\$499	36.0x17.0x16	D-2G+	BL, LW	16	35.3	111	21.8	17.0	42.5
1230	\$620	36.0x17.0x16	D-2A	BL	16	36.3	114	21.4	17.0	49.1
2912	\$165	Shield								

Pro Stock, Super Gas

1984	\$390	32.0x14.0x15	D-5	MS	14	32.4	101	17	14.4	39.3
1672	\$392	32.0x14.5x15	D-5	MS	14	32.8	103	17.7	14.8	39.4
1408	\$396	32.0x16.0x15	D-5	MS	15	32.4	102	18.4	16.0	39.6
2051	\$453	32.5x17.0x15	D-4A		15	32.5	100	20.8	17.2	41.1
2078	\$397	33.0x15.0x15	D-5	MS	14	33.2	104	17.5	15.0	40.6
2052	\$406	33.0x16.0x15	D-6		15	32.8	102	19.6	16.1	38.0
2053	\$453	33.0x17.0x15	D-4A	SS	15	32.8	102	20.6	17.3	42.9
2433	\$652	33.5x17.0x16	D-4A	BL, SS	16	33.4	105	21.5	17.7	43.0
2211	\$652	33.5x17.0x16	D-4A	BL, SS	16	33.4	105	21.2	17.5	42.5
2775	\$454	33.5x17.0x16	D-2A	BL	16	33.8	105	21.1	16.8	40.3

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall
ET - Extended tread life, **MC** - Motorcycle front, **BL** - Beadlock wheel required

Tire Code	MSRP	Tire Size	Compound	Comments	Rim Width	Overall Diam	Avg Circumference	Section Width	Tread Width	Weight
-----------	------	-----------	----------	----------	-----------	--------------	-------------------	---------------	-------------	--------

Stock, Super Stock

2790	\$215	28.0x9.0x15	D-5		8	28.0	88	10.7	9.0	21.3
2791	\$220	28.0x10.0x15	D-5		10	28.0	88	12.0	10.0	23.1
2796	\$255	29.0x11.0x15	D-5		10	29.0	91	12.8	10.9	25.1
2797	\$262	29.0x12.0x15	D-5		11	29.0	91	13.9	11.8	25.1
4465	\$292	30.0x10.5x15	D-8	R	10	29.6	93	13.3	10.5	23.5
4827	\$281	30.0x9.0x15	D-1A	R, LW	9	29.5	92.5	11.8	9.0	22.7
1909	\$288	30.0x9.0x15	D-5		8	30.7	96.5	12.4	9.0	25.0
2018	\$365	31.0x13.0x15	D-5	MS	12	30.6	96	15.6	12.8	33.4
4459	\$345	31.0x13.5x15	D-8		14	31.7	99.5	16.9	13.8	33.0
2019	\$369	31.0x14.0x15	D-5	MS	12	31.0	97	16.2	14.0	35.8
4461	\$374	32.0x14.0x15	D-8	R	14	32.1	101	17.2	13.8	32.4
1984	\$390	32.0x14.0x15	D-5		14	32.4	101	17.0	14.4	39.3
1672	\$392	32.0x14.5x15	D-5		14	32.8	103	17.7	14.8	39.4
2070	\$389	33.0x14.5x15	D-6		14	32.8	104	18.9	14.9	34.1

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall
ET - Extended tread life, **MC** - Motorcycle front, **BL** - Beadlock wheel required

Tire Code	MSRP	Tire Size	Compound	Comments	Rim Width	Overall Diam	Avg Circumference	Section Width	Tread Width	Weight
-----------	------	-----------	----------	----------	-----------	--------------	-------------------	---------------	-------------	--------

Competition Eliminator, Super Comp

2585	\$373	31.0x12.0x15	D-3		12	30.8	96.5	15.2	12.0	22.6
4513	\$453	31.0x16.0x15	D-8	R	15	31.7	99.5	19.4	16.3	35.0
1911	\$389	32.0x14.5x15	D-1		14	32.2	101	17.7	15.0	34.1
2051	\$399	32.5x17.0x15	D-4A	LW, SS	15	32.5	100	20.8	17.2	41.1
1288	\$384	33.0x12.0x15	D-7	HG	12	32.4	102	16.5	12.3	28.8
2070	\$389	33.0x14.5x15	D-6		14	32.8	104	18.9	14.9	34.1
2533	\$370	33.0x16.0x15	D-2A		15	32.4	104	19.9	16.3	39.6
2052	\$406	33.0x16.0x15	D-6		15	32.8	102	19.6	16.1	38.0
2534	\$381	33.0x17.0x15	D-2A		15	32.4	104	20.5	17.4	39.5
2775	\$454	33.5x17.0x16	D-2A	BL	16	33.6	105	21.1	16.8	40.3

Motorcycle

2980	\$203	25.0x7.0x18	D-6		6	25.4	80	7.0	6.6	11.3
------	-------	-------------	-----	--	---	------	----	-----	-----	------

Frontrunner

1445	\$191	22.0x2.5x17	HARD	ET	2.5	22.0	69.9	2.5	1.5	4.5
2904	\$267	22.0x4.0x17	HARD		2.5	22.9	72	3.4	3.1	5.2
1961	\$235	23.0x5.0x15	HARD		4	23.0	72.7	6.8	5.0	12.2
1962	\$200	24.0x5.0x15	HARD		4	24.0	75.8	6.8	5.0	11.3
2991	\$203	25.0x4.5x15	HARD	LW	4	25.0	78.5	6.5	4.5	11.6
1964	\$206	26.0x4.5x15	HARD		4	26.0	81.2	6.3	4.5	10.8
1965	\$207	27.0x4.5x15	HARD		4	27.0	84.8	7.9	4.5	13.5
1966	\$209	28.0x4.5x15	HARD		4	28.0	89.1	7.7	5.1	12.4

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall
ET - Extended tread life, **MC** - Motorcycle front, **BL** - Beadlock wheel required

Tire Code	MSRP	Tire Size	Compound	Comments	Rim Width	Overall Diam	Avg Circumference	Section Width	Tread Width	Weight
-----------	------	-----------	----------	----------	-----------	--------------	-------------------	---------------	-------------	--------

Landspeed

- Lightweight design for low rolling resistance
- Tubeless construction
- Longer life helps improve cost effectiveness

2952	\$620	21.0x5.0x15	HARD		4.5	21.3	68.5	5.4	4.1	10.0
2953	\$642	23.0x5.0x15	HARD		4.5	23.1	74.2	7.0	5.0	12.0
2954	\$649	25.0x4.5x15	HARD		4.5	24.8	79.0	6.7	4.0	12.0
2286	\$677	28.0x4.5x15	HARD		4.5	27.8	88.4	7.7	4.5	13.0
2291	\$262	28.0x10.0x15	HARD		9.5	28.0	88.0	13.6	10.0	22.5
2870	\$720	30.0x9.0x18	HARD	LW	6.5	30.0	93.0	8.5	3.0	16.5

	<u>Minimum</u>	<u>Max Load</u>	<u>Max Speed</u>
2952	50 psi	1200 lbs	300 mph
2953	70 psi	1700 lbs	300 mph
2954	70 psi	1700 lbs	300 mph
2286	70 psi	1700 lbs	300 mph
2291	70 psi	1700 lbs	300 mph
2870	70 psi	1700 lbs	320 mph

Goodyear Drag Tire Distributors

Shelby Carter-Maxwell, LLC (336) 884-0328
 3801 N. Main St.
 High Point, NC 27265

Carter-Maxwell, Inc. (405) 789-8253
 4215 N. Wilburn Ave.
 Bethany, OK 73008

Carroll Shelby Enterprises (702) 430-5160
 6895 Speedway Blvd. Building Z101
 Las Vegas, NV 89115

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall
ET - Extended tread life, **MC** - Motorcycle front, **BL** - Beadlock wheel required