

Size	Tire Code	Compound	Comments	MSRP	Rim Width	Overall Diam	Avg Circumference	Section Width	Tread Width	Weight
------	-----------	----------	----------	------	-----------	--------------	-------------------	---------------	-------------	--------

## Top Fuel & Funny Car

36.0x17.5-16	2681	D-2F	HG,BL	\$899	16.0	36.6	115.0	21.6	17.3	49.1
--------------	------	------	-------	-------	------	------	-------	------	------	------

## Pro Mod, Alcohol

34.5x17.0-16	2922	D-2F	LW,BL	\$535	16.0	34.7	109.0	21.0	17.0	42.1
36.0x17.0-16	1230	D-2A	HG,BL	\$620	16.0	36.3	114.0	21.4	17.0	49.9

## Pro Stock, Super Gas

32.0x14.0-15	1984	D-5	MS	\$390	14.0	32.1	101.0	17.0	14.4	39.3
32.0x14.5-15	1672	D-5	MS	\$392	14.0	32.8	103.0	17.7	14.8	39.4
32.0x16.0-15	1408	D-5	MS	\$396	15.0	32.5	102.0	18.4	16.0	39.6
33.0x15.0-15	2078	D-5	MS	\$397	14.0	33.1	104.0	17.5	15.0	40.6
33.0x16.0-15	2052	D-6		\$406	15.0	32.5	102.0	19.6	16.1	38.0
33.0x17.0-15	2053	D-4A	SS	\$453	15.0	32.5	102.0	20.6	17.3	42.9
33.5x17.0-16	2211	D-4A	SS,BL	\$652	16.0	33.4	105.0	20.8	17.4	43.1
33.5x17.0-16	2775	D-2A	BL	\$454	16.0	33.4	105.0	21.1	16.8	39.1
34.5x17.0-16	2922	D-2F	LW,BL	\$535	16.0	34.7	109.0	21.0	17.0	42.1

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall  
**ET** - Extended tread life, **MC** - Motorcycle front, **BL** - Beadlock wheel required

Size	Tire Code	Compound	Comments	MSRP	Rim Width	Overall Diam	Avg Circumference	Section Width	Tread Width	Weight
------	-----------	----------	----------	------	-----------	--------------	-------------------	---------------	-------------	--------

## Stock, Super Stock

28.0x9.0-15	2790	D-5		\$215	8.0	28.0	88.0	10.7	9.0	21.3
28.0x10.0-15	2791	D-5		\$220	10.0	28.0	88.0	12.0	10.0	23.1
29.0x11.0-15	2796	D-5		\$255	10.0	29.0	91.0	12.8	10.9	25.1
29.0x12.0-15	2797	D-5		\$262	11.0	29.0	91.0	13.0	11.8	26.3
30.0x9.0-15	4457	D-1A	R,LW	\$281	9.0	29.9	94.0	12.0	9.0	22.7
31.0x13.0-15	2018	D-5	MS	\$365	12.0	30.6	96.0	15.6	12.8	33.4
31.0x14.0-15	2019	D-5	MS	\$369	12.0	30.9	97.0	16.2	14.0	35.8
33.0x14.5-15	2070	D-6		\$389	14.0	33.1	104.0	18.9	14.9	34.1

## Competition Eliminator, Super Comp

32.0x14.5-15	1911	D-1		\$389	14.0	32.1	101.0	17.7	15.0	34.1
33.0x12.0x15	1288	D-7	HG	\$384	12.0	32.5	102.0	16.5	12.3	28.8
33.0x14.5-15	2070	D-6		\$389	14.0	33.1	104.0	18.9	14.9	34.1
33.0x16.0-15	2533	D-2A		\$370	15.0	33.7	106.0	20.2	16.5	40.5
33.0x17.0-15	2534	D-2A		\$381	16.0	33.7	106.0	21.2	17.5	41.2
33.0x17.0-15	2051	D-4A	LW,SS	\$453	15.0	31.8	100.0	20.8	17.2	41.1
33.0x17.0-15	2053	D-4A	SS	\$453	15.0	32.5	102.0	20.6	17.3	42.9
33.5x17.0-16	2775	D-2A	BL	\$454	16.0	33.4	105.0	21.1	16.8	39.1
33.5x17.0-16	2211	D-4A	SS,BL	\$652	16.0	33.4	105.0	20.8	17.4	43.1
34.5x17.0-16	2922	D-2F	LW,BL	\$535	16.0	34.7	109.0	21.0	17.0	42.1

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall  
**ET** - Extended tread life, **MC** - Motorcycle front, **BL** - Beadlock wheel required

Size	Tire Code	Compound	Comments	MSRP	Rim Width	Overall Diam	Avg Circumference	Section Width	Tread Width	Weight
------	-----------	----------	----------	------	-----------	--------------	-------------------	---------------	-------------	--------

## Eagle Drag Radial

30.0x9.0-15	4457	D-1A	R,LW	\$281	9.0	29.8	94.0	12.0	9.0	22.7
-------------	------	------	------	-------	-----	------	------	------	-----	------

## Motorcycle

25.0x7.0-18	2982	D-3		\$215	6.0	25.5	80.0	7.0	6.6	11.3
-------------	------	-----	--	-------	-----	------	------	-----	-----	------

## Frontrunner

22.0x2.5-17	1445	Hard	ET	\$191	2.5	22.2	69.9	2.5	1.5	4.5
22.0x4.0-17	2904	Hard		\$267	2.5	22.9	72.0	3.4	3.1	5.2
23.0x5.0-15	1961	Hard		\$235	4.0	23.1	72.7	6.8	5.0	12.2
24.0x5.0-15	1962	Hard		\$200	4.0	24.1	75.8	6.8	5.0	11.3
25.0x4.5-15	2991	Hard	LW	\$203	4.0	25.3	79.5	6.5	4.5	9.8
26.0x4.5-15	1964	Hard		\$206	4.0	25.8	81.2	6.3	4.5	10.8
27.0x4.5-15	1965	Hard		\$207	4.0	27.0	84.8	7.9	4.5	13.5
28.0x4.5-15	1966	Hard		\$209	4.0	28.4	89.1	7.7	5.1	12.4

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall  
**ET** - Extended tread life, **MC** - Motorcycle front, **BL** - Beadlock wheel required

## Eagle Land Speed

- Lightweight design for lower rolling resistance
- Tubeless construction means lightweight performamnce and less maintenance
- Longer life helps improve cost effectiveness

Size	Tire Code	Compound	MSRP	Rim Width	Overall Diam	Section Width	Tread Width	Weight	Min Inflation (psi)	Max Load (lbs)	Max Speed (MPH)
------	-----------	----------	------	-----------	--------------	---------------	-------------	--------	---------------------	----------------	-----------------

### Eagle Land Speed

21.0x5.0-15	2282	Hard	\$620	4.5	21.3	5.4	4.1	10.0	50.0	1200	300
23.0x5.0-15	2283	Hard	\$642	4.5	23.1	7.0	5.0	12.0	70.0	1700	300
25.0x4.5-15	2284	Hard	\$649	4.5	24.8	6.7	4.0	12.0	70.0	1700	300
28.0x4.5-15	2286	Hard	\$677	4.5	27.8	7.7	4.5	13.0	70.0	1700	300
28.0x10.0-15	2291	Hard	\$260	9.0	28.0	13.2	10.3	22.0	70.0	1700	300

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall  
**ET** - Extended tread life, **MC** - Motorcycle front, **BL** - Beadlock wheel required