

| Size | Tire Code | Compound | Comments | MSRP | Rim Width | Overall Diam | Avg Circumference | Section Width | Tread Width | Weight |
|------|-----------|----------|----------|------|-----------|--------------|-------------------|---------------|-------------|--------|
|------|-----------|----------|----------|------|-----------|--------------|-------------------|---------------|-------------|--------|

Top Fuel & Funny Car

| | | | | | | | | | | |
|--------------|------|------|-------|-------|------|------|-------|------|------|------|
| 36.0x17.5-16 | 2681 | D-2F | HG,BL | \$832 | 16.0 | 36.6 | 115.0 | 21.6 | 17.3 | 49.1 |
|--------------|------|------|-------|-------|------|------|-------|------|------|------|

Pro Mod, Alcohol

| | | | | | | | | | | |
|--------------|------|------|-------|-------|------|------|-------|------|------|------|
| 34.5x17.0-16 | 2922 | D-2F | LW,BL | \$499 | 16.0 | 34.7 | 109.0 | 21.0 | 17.0 | 42.1 |
| 36.0x17.0-16 | 1230 | D-2A | HG,BL | \$573 | 16.0 | 36.3 | 114.0 | 21.4 | 17.0 | 49.9 |

Pro Stock, Super Gas

| | | | | | | | | | | |
|--------------|------|------|-------|-------|------|------|-------|------|------|------|
| 32.0x14.0-15 | 1984 | D-5 | MS | \$361 | 14.0 | 32.1 | 101.0 | 17.0 | 14.4 | 39.3 |
| 32.0x14.5-15 | 1672 | D-5 | MS | \$363 | 14.0 | 32.8 | 103.0 | 17.7 | 14.8 | 39.4 |
| 32.0x16.0-15 | 1408 | D-5 | MS | \$365 | 15.0 | 32.5 | 102.0 | 18.4 | 16.0 | 39.6 |
| 33.0x15.0-15 | 2078 | D-5 | MS | \$367 | 14.0 | 33.1 | 104.0 | 17.5 | 15.0 | 40.6 |
| 33.0x16.0-15 | 2052 | D-6 | | \$375 | 15.0 | 32.5 | 102.0 | 19.6 | 16.1 | 38.0 |
| 33.0x17.0-15 | 2053 | D-4A | SS | \$419 | 15.0 | 32.5 | 102.0 | 20.6 | 17.3 | 42.9 |
| 33.5x17.0-16 | 2200 | D-4A | SS,BL | \$602 | 16.0 | 33.4 | 105.0 | 20.8 | 17.4 | 43.1 |
| 33.5x17.0-16 | 2774 | D-2A | BL | \$428 | 16.0 | 33.4 | 105.0 | 21.1 | 16.8 | 39.1 |
| 34.5x17.0-16 | 2922 | D-2F | LW,BL | \$499 | 16.0 | 34.7 | 109.0 | 21.0 | 17.0 | 42.1 |

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall
ET - Extended tread life, **MC** - Motorcycle front, **BL** - Beadlock wheel required

| Size | Tire Code | Compound | Comments | MSRP | Rim Width | Overall Diam | Avg Circumference | Section Width | Tread Width | Weight |
|------|-----------|----------|----------|------|-----------|--------------|-------------------|---------------|-------------|--------|
|------|-----------|----------|----------|------|-----------|--------------|-------------------|---------------|-------------|--------|

Stock, Super Stock

| | | | | | | | | | | |
|--------------|------|------|------|-------|------|------|-------|------|------|------|
| 28.0x9.0-15 | 2790 | D-5 | | \$191 | 8.0 | 28.0 | 88.0 | 10.7 | 9.0 | 21.3 |
| 28.0x10.0-15 | 2791 | D-5 | | \$195 | 10.0 | 28.0 | 88.0 | 12.0 | 10.0 | 23.1 |
| 29.0x11.0-15 | 2796 | D-5 | | \$230 | 10.0 | 29.0 | 91.0 | 12.8 | 10.9 | 25.1 |
| 29.0x12.0-15 | 2797 | D-5 | | \$236 | 11.0 | 29.0 | 91.0 | 13.0 | 11.8 | 26.3 |
| 30.0x9.0-15 | 4456 | D-4B | R,LW | \$260 | 9.0 | 29.9 | 94.0 | 12.0 | 9.0 | 22.7 |
| 31.0x13.0-15 | 2018 | D-5 | MS | \$338 | 12.0 | 30.6 | 96.0 | 15.6 | 12.8 | 33.4 |
| 31.0x14.0-15 | 2019 | D-5 | MS | \$341 | 12.0 | 30.9 | 97.0 | 16.2 | 14.0 | 35.8 |
| 33.0x14.5-15 | 2070 | D-6 | | \$355 | 14.0 | 33.1 | 104.0 | 18.9 | 14.9 | 34.1 |

Competition Eliminator, Super Comp

| | | | | | | | | | | |
|--------------|------|------|-------|-------|------|------|-------|------|------|------|
| 32.0x14.5-15 | 1911 | D-1 | | \$360 | 14.0 | 32.1 | 101.0 | 17.7 | 15.0 | 34.1 |
| 33.0x14.5-15 | 2070 | D-6 | | \$355 | 14.0 | 33.1 | 104.0 | 18.9 | 14.9 | 34.1 |
| 33.0x16.0-15 | 2533 | D-2A | | \$342 | 15.0 | 33.7 | 106.0 | 20.2 | 16.5 | 40.5 |
| 33.0x17.0-15 | 2534 | D-2A | | \$352 | 16.0 | 33.7 | 106.0 | 21.2 | 17.5 | 41.2 |
| 33.0x17.0-15 | 2053 | D-4A | SS | \$419 | 15.0 | 32.5 | 102.0 | 20.6 | 17.3 | 42.9 |
| 33.5x17.0-16 | 2774 | D-2A | BL | \$428 | 16.0 | 33.4 | 105.0 | 21.1 | 16.8 | 39.1 |
| 33.5x17.0-16 | 2200 | D-4A | SS,BL | \$602 | 16.0 | 33.4 | 105.0 | 20.8 | 17.4 | 43.1 |
| 34.5x17.0-16 | 2922 | D-2F | LW,BL | \$499 | 16.0 | 34.7 | 109.0 | 21.0 | 17.0 | 42.1 |

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall
ET - Extended tread life, **MC** - Motorcycle front, **BL** - Beadlock wheel required

| Size | Tire Code | Compound | Comments | MSRP | Rim Width | Overall Diam | Avg Circumference | Section Width | Tread Width | Weight |
|--------------|-----------|----------|----------|-------|-----------|--------------|-------------------|---------------|-------------|--------|
| 30.0x9.0-15 | 4456 | D-4B | R,LW | \$260 | 9.0 | 29.8 | 94.0 | 12.0 | 9.0 | 22.7 |
| 32.0x14.0-15 | 4461 | D-8 | R | \$374 | 14.0 | 32.1 | 101.0 | 17.2 | 13.8 | 31.0 |
| 31.0x16.0-15 | 4513 | D-8 | R | \$434 | 14.0 | 33.0 | 103.8 | 17.4 | 14.5 | 35.0 |
| 30.0x10.5-15 | 4465 | D-8 | R | \$275 | 10.0 | 29.6 | 93.0 | 13.25 | 10.5 | 23.5 |

Frontrunner

| | | | | | | | | | | |
|-------------|------|------|----|-------|-----|------|------|-----|-----|------|
| 22.0x2.5-17 | 1445 | Hard | ET | \$172 | 2.5 | 22.2 | 69.9 | 2.5 | 1.5 | 4.5 |
| 22.0x4.0-17 | 2904 | Hard | | \$242 | 2.5 | 22.9 | 72.0 | 3.4 | 3.1 | 5.2 |
| 23.0x5.0-15 | 1961 | Hard | | \$212 | 4.0 | 23.1 | 72.7 | 6.8 | 5.0 | 12.2 |
| 24.0x5.0-15 | 1962 | Hard | | \$180 | 4.0 | 24.1 | 75.8 | 6.8 | 5.0 | 11.3 |
| 25.0x4.5-15 | 2991 | Hard | LW | \$183 | 4.0 | 25.3 | 79.5 | 6.5 | 4.5 | 9.8 |
| 26.0x4.5-15 | 1964 | Hard | | \$186 | 4.0 | 25.8 | 81.2 | 6.3 | 4.5 | 10.8 |
| 27.0x4.5-15 | 1965 | Hard | | \$187 | 4.0 | 27.0 | 84.8 | 7.9 | 4.5 | 13.5 |
| 28.0x4.5-15 | 1966 | Hard | | \$189 | 4.0 | 28.4 | 89.1 | 7.7 | 5.1 | 12.4 |

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall
ET - Extended tread life, **MC** - Motorcycle front, **BL** - Beadlock wheel required

Eagle Land Speed

- Lightweight design for lower rolling resistance
- Tubeless construction means lightweight performamnce and less maintenance
- Longer life helps improve cost effectiveness

| Size | Tire Code | Compound | MSRP | Rim Width | Overall Diam | Section Width | Tread Width | Weight | Min Inflation (psi) | Max Load (lbs) | Max Speed (MPH) |
|------|-----------|----------|------|-----------|--------------|---------------|-------------|--------|---------------------|----------------|-----------------|
|------|-----------|----------|------|-----------|--------------|---------------|-------------|--------|---------------------|----------------|-----------------|

Eagle Land Speed

| | | | | | | | | | | | |
|--------------|------|------|-------|-----|------|------|------|------|------|------|-----|
| 21.0x5.0-15 | 2282 | Hard | \$573 | 4.5 | 21.3 | 5.4 | 4.1 | 10.0 | 50.0 | 1200 | 300 |
| 23.0x5.0-15 | 2283 | Hard | \$594 | 4.5 | 23.1 | 7.0 | 5.0 | 12.0 | 70.0 | 1700 | 300 |
| 25.0x4.5-15 | 2284 | Hard | \$600 | 4.5 | 24.8 | 6.7 | 4.0 | 12.0 | 70.0 | 1700 | 300 |
| 28.0x4.5-15 | 2286 | Hard | \$626 | 4.5 | 27.8 | 7.7 | 4.5 | 13.0 | 70.0 | 1700 | 300 |
| 28.0x10.0-15 | 2291 | Hard | \$247 | 9.0 | 28.0 | 13.2 | 10.3 | 22.0 | 70.0 | 1700 | 300 |

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall
ET - Extended tread life, **MC** - Motorcycle front, **BL** - Beadlock wheel required